

FIG. 1A
(PRIOR ART)




FIG. 1B
(PRIOR ART)




FIG. 2B




FIG. 2A




FIG. 2D






FIG. 2C



PRESSURE DISTRIBUTION ON A CIRCULAR CYLINDER

FIG. 3




PRESSURE RISE TO SEPARATION
(FROM HUBBART & BANGERT, 1970)

FIG. 4



DRILLING RISER BLC SYSTEM
PRELIMINARY CHARACTERISTICS ESTIMATES



CURRENT: 6.0 fps
DIAMETER: 54. in.
JMR: 6
Cf FACTOR: 2
EHP/ft.: 1.77
Cmu: 0.0531

—●— jet vel, fps
—▲— WHP/ft.
—■— gps/ft.
—▼— Uj/Ues

FIG. 5




FIG. 6A




FIG. 6B





FIG. 7




FIG. 8




FIG. 9A




FIG. 9B




FIG. 10





FIG. 11

U.S. PAT. & TRADEMARK OFFICE
NOV 17 2023




FIG. 12A




FIG. 12B





FIG. 13






FIG. 14B




FIG. 14C




FIG. 14D




FIG. 14E




FIG. 14F




FIG. 15A






FIG. 15B






FIG. 16A




FIG. 16B




FIG. 16C




FIG. 16D




FIG. 16E